

SECURITHERM Securitouch thermostatic shower-bath mixer

Ref. H9752S

Dual control thermostatic shower mixer








DESCRIPTION

SECURITHERM Securitouch thermostatic shower-bath mixer - Ref. H9752S





SECURITHERM dual control thermostatic shower-bath mixer. Thermostatic mixer with anti-scalding safety: shuts off automatically if cold or hot water supply fails. Securitouch thermal insulation prevents burns. Scale-resistant thermostatic cartridge for temperature adjustment. ¼-turn ceramic head for flow rate adjustment. Temperature control from 25 - 41°C. Double temperature limiter: first limiter set at 38°C (can be overridden), second limiter set at 41°C. Straight forward thermal shock procedure without removing the control knob or shutting off the cold water supply. Thermostatic mixer fitted with an automatic diverter with low pressure lock maintains the shower position even if the flow rate is too low. Chrome-plated brass body and ERGO control knobs. M1/2" shower outlet. F3/4" inlets with integrated filters and non-return valves. Wall-mounted mixer with M1/2" M3/4" offset standard connectors. 10-year warranty.

TECHNICAL CHARACTERISTICS

SECURITHERM Securitouch thermostatic shower-bath mixer - Ref. H9752S

Connector	M1/2"
Technology	SECURITHERM dual control thermostatic mixer, Securitouch
Width	286mm
Temperature limiter	41°C
Finish	Chrome-plated brass
Norms	   
Warranty	

ADVANTAGES

-  SECURITHERM: Optimum anti-scalding safety
-  Double maximum temperature limiter
-  Securitouch anti-scalding thermal insulation
-  Thermostatic: total temperature stability

