


Geberit DuofixBasic element for wall-hung WC, 112 cm, with Delta concealed cistern 12 cm



Application purposes

- For drywall construction
- · For installation in part or room-height prewall installations
- · For installation in room-height installation walls
- For wall-hung WCs with connection dimensions in accordance with EN 33:2011
- For wall-hung WCs with projection up to 62 cm
- For single flush, dual flush or stop-and-go flush
- For floor constructions 0-20 cm

Characteristics

- · Self-supporting frame, powder-coated
- Frame top open
- Frame with Ø 9 mm drilling holes for fastening in wood frame construction
- Frame with holes to receive Geberit Duofix wall anchors for elements with frame top open

- Frame prepared for support brackets for WC ceramic appliances with small contact surfaces
- Galvanized feet
- Feet adjustable 0–20 cm
- Foot plates made of plastic
- · Foot plate depth suitable for installation in U-profiles UW 50
- Concealed cistern with front actuation
- Concealed cistern, fully insulated against condensation
- · Immediate post flush possible with factory setting
- Water supply connection on the rear or top centre
- With conduit pipe for feed pipe for connection of Geberit AquaClean shower toilets
- · Fastening option for electrical connection

Technical data

Flush volume, factory setting	6 and 3 l
Flush volume large, adjustment range	4.5 / 6 / 7.5
Flush volume small, adjustment range	3-41

Scope of delivery

- Angle stop valve R 1/2", compatible with MF, with adapter ring
- Protection box for service opening, made of polystyrene foam
- 2 distance bolts
- · Connection set for WC, ø 90 mm
- Connection bend 90° made of PE-HD, ø 90 mm

- · Adapter socket made of PE-HD, ø 90 / 110 mm
- 2 protection plugs
- 2 threaded rods M12
- Fastening material

Art. no.	В	н	т
111.153.00.1	50 cm	112 cm	12 cm

Accessories

- · Geberit set of support brackets for WC ceramic appliances with small contact surfaces
- · Geberit DuofixBasic set of wall anchors for single installation
- · Geberit Duofix set of wall anchors for single installation, with crossbar, clip-on

()

· Actuator plate has to be ordered separately