


Geberit Mapress Carbon Steel elbow adapter 90° with male thread



Example image



Application purposes

- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For district heating water ≤ 120 °C
- For extinguishing water (wet)
- For sprinklers (wet)
- For compressed air (oil purity class 3)
- For technical building systems, industry and shipbuilding

Characteristics

- Pressing indicator
- Leaky if unpressed
- Outside zinc-plated
- Seal ring made of CIIR, black
- Pressing socket with transparent protection plug

Technical data

Product material | Non-alloy steel 1.0034 E195 (EN 10305)

Art. no.	DN	d, ø	R	arc	L	H	Z
21611	10	12 mm	3/8 "	90 °	3.2 cm	2.5 cm	1.5 cm
21612	12 / 10	15 mm	3/8 "	90 °	3.6 cm	2.6 cm	1.6 cm
21613	12 / 15	15 mm	1/2 "	90 °	3.5 cm	3.1 cm	1.5 cm
21615	15	18 mm	1/2 "	90 °	3.7 cm	3.1 cm	1.7 cm
21618	20	22 mm	3/4 "	90 °	4.1 cm	3.5 cm	2 cm
21609	25 / 20	28 mm	3/4 "	90 °	5.8 cm	5 cm	3.5 cm
21610	25	28 mm	1 "	90 °	5.8 cm	5.4 cm	3.5 cm