

Qty.	Description
1	<p data-bbox="204 338 491 365">UNILIFT AP50.50.08.A3.V</p> <div data-bbox="295 383 486 689" style="text-align: center;">  </div> <p data-bbox="592 685 1062 707" style="text-align: center;">Note! Product picture may differ from actual product</p> <p data-bbox="204 719 555 775">Product No.: 96010933 Submersible drainage pump type</p> <p data-bbox="204 804 718 949">Vertical single-stage stainless steel submersible pump with vertical discharge port and integrated submersible 3-phase totally enclosed motor in insulation class F. The pump is fitted with a suction strainer.</p> <p data-bbox="204 983 786 1160">The pump is supplied with a control box including motor starter, a motor protection and a float switch for automatic start/stop of the pump . The float switch contains 10 m cable. And there is a 0.8m main cable connected to the box (see electrical data for optional CEE plug).</p> <p data-bbox="204 1191 663 1308">The impeller is a V impeller for 50 mm free passage suitable for pumping groundwater, surface water, rain water and similar liquids.</p> <p data-bbox="204 1339 722 1424">The pump has a double shaft seal and an intermediate oil chamber pre-filled with non-toxic special oil.</p> <p data-bbox="204 1458 710 1574">The pump has a riser pipe, a cooling jacket for continuous cooling of the motor by the pumped liquid and long-life deep-groove greased-for-life ball bearings.</p> <p data-bbox="204 1608 722 1785">The pump is ready for use as it is fitted with carrying handle and is supplied with a 10 m mains cable. The mains cable is of the plug type with glass sealing compound in the socket to prevent penetration of humidity into the stator windings.</p> <p data-bbox="204 1816 793 1933">Liquid: Pumped liquid: Any Newtonian liquid Liquid temperature range: 0 .. 55 °C Density: 998.2 kg/m³</p> <p data-bbox="204 1964 641 2049">Technical: Type of impeller: V Maximum particle size: 50 mm</p>

Qty.	Description
	Materials: Pump housing: Stainless steel DIN W.-Nr. 1.4301 AISI 304 Impeller: Stainless steel DIN W.-Nr. 1.4301 AISI 304 Cable union: Brass CW602N C35330 Installation: Range of ambient temperature: 0 .. 55 °C Pump outlet: Rp 2 Maximum installation depth: 7 m Electrical data: Power input - P1: 1.2 kW Mains frequency: 50 Hz Rated voltage: 3 x 400 V Rated current: 2 A Cos phi - power factor: 0.87 Rated speed: 2820 rpm Enclosure class (IEC 34-5): IP68 Insulation class (IEC 85): F Length of cable: 10 m Type of cable plug: NONE Others: Net weight: 17.6 kg Gross weight: 19.2 kg Danish VVS No.: 391322312 Swedish RSK No.: 5880119 Country of origin: HU Custom tariff no.: 84137021