



The HANSA VANTIS is the perfect fit for any bathroom, with a proven expert quality you can rely on, no matter your specific needs. Durable and long-lasting in both design and service life, this faucet brings you joy and confidence for years to come.
Functional considerations and a dedicated level of detail offer a new user experience.

Easy to install with the 3S installation system.
High quality
Sleek design
Made in Europe

Washbasin faucet with maximum comfort

- Deck mounted
- Chrome
- Fixed spout
- PCA® - constant flow rate regardless of pressure variations
- Single operating lever/handle, Pin shape, Hot/Cold symbols
- Limitation option for maximum temperature and flow-rate
- ø 30 mm ceramic cartridge for flow and temperature control
- Flexible inlet pipes
- Inner body made of DZR brass, 3S-installation system for safe and simple mounting
- Without pop-up waste

TECHNICAL DATA

FLOW PROPERTIES

Flow-rate at 3 bar (with flow controller) **6.0 l/min**

TECHNICAL PROPERTIES

Hot water supply **max. +70°C**
Working pressure **0.5-10 bar**
Connection size **G3/8**
Projection **109 mm**
Backflow prevention (EN1717) **AA**
Material **Brass**

REGULATIONS

EN standard **EN 817**
Noise class **I (ISO 3822)**

APPROVALS AND DECLARATIONS

DVGW **DW-6506DN0781**
Declaration of conformity **DoC**
EPD **S-P-06391**

SUSTAINABILITY

EPD module A1-A3 (kg CO2 eq.) **7,30**
EPD module A4 (kg CO2 eq.) **0,20**
EPD module B7 (kg CO2 eq.) **1854,00**
EPD module C2 (kg CO2 eq.) **0,01**
EPD module C3 (kg CO2 eq.) **0,02**
EPD module C4 (kg CO2 eq.) **0,06**
EPD module D (kg CO2 eq.) **-5,19**

